



6CL6

POWER PENTODE

MINIATURE TYPE

6CL6

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage 6.3 ac or dc volts
Current 0.65 amp

Direct Interelectrode Capacitances (without external shield):

Grid No.1 to Plate . . 0.120 μ f
Input 11 μ f
Output 5.5 μ f

Characteristics, Amplifier Class A₁:


Plate Voltage 250 volts
Grid No.3 Connected to cathode at socket
Grid-No.2 Voltage 150 volts
Grid-No.1 Voltage -3 volts
Peak AF Grid-No.1 Signal Voltage 3 volts
Zero-Signal DC Plate Current 30 ma
Max.-Signal DC Plate Current 31 ma
Zero-Signal DC Grid-No.2 Current 7 ma
Max.-Signal DC Grid-No.2 Current 7.2 ma
Plate Resistance (Approx.) 0.15 megohm
Transconductance 11000 μ hos
Grid-No.1 Voltage (Approx.) for
plate current of 10 μ amp -14 volts
Load Resistance 7500 ohms
Total Harmonic Distortion 8 per cent
Max.-Signal Power Output 2.8 watts

Mechanical:

Mounting Position Any
Maximum Overall Length 2-5/8"
Maximum Seated Length 2-3/8"
Length, Base Seat to Bulb Top (excluding tip) 2" \pm 3/32"
Maximum Diameter 7/8"
Bulb T-6-1/2
Base Small-Button Noval 9-Pin (JETEC No.E9-1)

BOTTOM VIEW

Pin 1 - Cathode
Pin 2 - Grid No.1
Pin 3 - Grid No.2
Pin 4 - Heater
Pin 5 - Heater



Pin 6 - Plate
Pin 7 - Grid No.3,
Int.Shield
Pin 8 - Grid No.2
Pin 9 - Grid No.1

AMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE 300 max. volts
PLATE SUPPLY VOLTAGE 300 max. volts
GRID-No.3 (SUPPRESSOR)VOLTAGE 0 max. volts

SEPT. 1, 1952

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

TENTATIVE DATA

6CL6



6CL6

POWER PENTODE

GRID-No.2 (SCREEN) VOLTAGE	See Rating Curve at front of this Section
GRID-No.2 SUPPLY VOLTAGE	300 max. volts
GRID-No.1 (CONTROL-GRID) VOLTAGE:	
Negative bias value	50 max. volts
Positive bias value	0 max. volts
PLATE DISSIPATION	7.5 max. watts
GRID-No.2 INPUT	1.7 max. watts
PEAK HEATER-CATHODE VOLTAGE:	
Heater negative with respect to cathode .	90 max. volts
Heater positive with respect to cathode .	90 max. volts
BULB TEMPERATURE (At hottest point on bulb surface)	200 max. °C

Typical Operation in 4-Mc Bandwidth Video Amplifier

Circuit of Fig. 1:

Plate Supply Voltage	300	volts
Grid No.3	Connected to cathode at socket	
Grid-No.2 Supply Voltage	300	volts
Grid-No.1 Bias Voltage	-2	volts
Grid-No.1 Signal Voltage (Peak to Peak) .	3	volts
Grid-No.2 Resistor	24000	ohms
Grid-No.1 Resistor	0.1	megohm
Load Resistor	3900	ohms
Zero-Signal Plate Current	30	ma
Zero-Signal Grid-No.2 Current	7.0	ma
Voltage Output (Peak to Peak)	132	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1 max. megohm
For cathode-bias operation	0.5 max. megohm

SEPT. 1, 1952

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


TENTATIVE DATA



6CL6

POWER PENTODE

Fig. 1 - Typical Video Voltage Amplifier Circuit
Having Bandwidth of 4 Mc.



92CS-7804

C1: 0.1 μ f, 400 volts

C2: 4 μ f, 400 volts

L1: Peaking Coil, 180 μ h

L2: Peaking Coil, 120 μ h

R1: 100000 ohms, 0.5 watt

R2: 47000 ohms, 0.5 watt

R3: 24000 ohms, 2 watts

R4: 3900 ohms, 5 watts

non-inductive type

Devices and arrangements shown or described herein may use patents of RCA or others. Information contained herein is furnished without responsibility by RCA for its use and without prejudice to RCA's patent rights.

SEPT. 1, 1952

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


CE-7804

6CL6



6CL6

AVERAGE PLATE CHARACTERISTICS WITH EC2 AS VARIABLE



MAY 22, 1952

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-7803

6CL6



6CL6

AVERAGE CHARACTERISTICS



MAY 21, 1952

TUBE DEPARTMENT
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-7801




6CL6

6CL6

AVERAGE PLATE CHARACTERISTICS TRIODE CONNECTION

$E_f = 6.3$ VOLTS
GRID N° 3 CONNECTED TO CATHODE
GRID N° 2 CONNECTED TO PLATE



MAY 26, 1952

PLATE MILLIAMPERES
TUBE DEPARTMENT

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-7808